

VENTILATORI CENTRIFUGHI SVM 2p

Tipo • Type • Type • Typ • Tipo		P inst. [kW]	n	LpA [dB(A)]	Tolleranza sulla portata ±5% • Tolérance sur le débit ±5% • Load tolerance ±5% • Durchsatztoleranz ±5% • Tolerancia respecto caudal ±5%																											
Ventilatore • Ventilateur • Fan • Ventilator • Ventilador	Motore • Moteur • Motor • Motor • Motor				Q [m³/h]																											
					360	400	430	470	540	650	720	790	865	935	1080	1225	1370	1440	1620	1800	2160	2520	2880	3240	3600	3960	4320	4680	5400	6120	7200	7920
					pt[mmH₂O]																											
220/2	63	0,18	2820	54	70	69	68	66	63	56	51	44																				
250/2	71	0,37	2820	59				97	96	93	91	88	86	83	73	62	47															
280/2	80	0,75	2850	61						122	121	120	120	118	114	110	103	100	88	73												
310/2	90	1,5	2920	65										164	161	158	155	153	149	144	128	105										
350/2	90	2,2	2920	68													204	204	205	202	195	184	169	152	130							
400/2	112	4	2940	71															285	284	279	271	260	247	232	214	195	153	109			
450/2	132	7,5	2940	73																			346	344	339	331	323	300	271	216	178	