

3.5" touch control panel with color graphic display

COD: PNLNTR35000000



3.5" touch control panel with color graphic display that can control up to 4 units.

Insight

3.5" touch control panel is useful for monitoring speed, direction of rotation and reporting any faults.

- It has an RS-485 Modbus connection
- Power supply at 24 VaC 50/60Hz (max 4 VA) or 12 ÷ 30VDC (max 2W)
- IP30



Technical Data

Code	Power W	Power supply Vdc	Power supply Hz
PNLCNTR35000000	2	12:30 p.m.	50/60



Related accessories



Potentiometer equipped with a bipolar ON/OFF switch

POTINTBIP000000

Remote potentiometer with front knob for manual adjustment of fan speed provided with two-pole switch (ON/OFF) and yellow front LED.



Potentiometer equipped with two bipolar ON/OFF switches

POTINTBIP200000

Remote potentiometer with front knob for manual adjustment of fan speed.



Related Products



HVLS industrial 5-blade ceiling fan APBG5

SMHS000000000000

APBG5 5-Blade Industrial Ceiling Fan

- 5 Blades Extruded Aluminum Anodized Against Corrosion Constant Section
- Increased Air Distribution Cone
- Three-phase Brushless EC motor equipped with Integrated Electronic System and EMC filters
- 3 Sizes with Diameters 3.6m / 5.4m / 7.3m
- Air Flow Rates up to 438,818 m³/h (AMCA230-99)
- 110 RPM Max
- Pot. Max Ass. 0.75 kW



HVLS industrial 5-blade ceiling fan APBG5S

SWHS000000000000

HVLS Industrial 5-Blade Ceiling Fan APBG5S

- 5 Blades Extruded Aluminum Shaped Profile
- Narrow Cone Air Distribution
- Three-phase Brushless EC motor equipped with Integrated Electronic System and EMC filters 3
- Sizes with Diameters 4m / 5m / 6m
- Air Flow Rates up to 529,464 m³/h (AMCA230-99)
- 120 RPM Max
- Pot. Max Ass. 1.4 kW
- Suitable for continuous duty S1



Industrial 3-blade ceiling fan HVLS3

SLHS000000000000

HVLS 3-Blade Industrial Ceiling Fans.

- 3 Blades Extruded in Anodized Aluminum against Corrosion with Constant Cross Section
- Precabled 3-phase Brushless EC motor equipped with Integrated Electronic System and EMC3 filters
- Sizes with Diameters 2.4m / 3m / 3.6m
- Air Flow Rates up to 134,271 m³/h (AMCA230-99)200
- Max RPM
- Pot. Max Ass. 0.7 kW
- Suitable for continuous duty S1.

