

# Control panel with temperature probe included and humidity probe on request

COD:

PNCSNDUMID00000



Controller to control ventilation units according to temperature degree and THI level.

## Insight

- Features "Shower Control" and "Auxiliary Ventilation Activation" modes.
- 0-10V regulation
- 230Vac - 50/60Hz
- Can control up to 10 units
- IP65 wall-mounted casing
- **Dimensions:** 160x110x81 mm
- **Included:** temperature probe
- On **request:** humidity probe



## Dimensions

Code	Dimensions mm
PNCSNDUMID00000	160 x 110 x 81

## Technical Data

Code	Power supply V	Power supply Hz
PNCSNDUMID00000	0-10	50/60



## Related Products



### SEQA1400 High Flow Axial Fan

SEQA140000000000

High-flow axial fans suitable for wall or overhead installation to create a uniform indoor climate and recirculate air in commercial and industrial buildings, farms, barns, and greenhouses.



### HVLS industrial 5-blade ceiling fan APBG5S

SWHS000000000000

HVLS Industrial 5-Blade Ceiling Fan APBG5S

- 5 Blades Extruded Aluminum Shaped Profile
- Narrow Cone Air Distribution
- Three-phase Brushless EC motor equipped with Integrated Electronic System and EMC filters 3
- Sizes with Diameters 4m / 5m / 6m
- Air Flow Rates up to 529,464 m<sup>3</sup>/h (AMCA230-99)
- 120 RPM Max
- Pot. Max Ass. 1.4 kW
- Suitable for continuous duty S1



### HVLS industrial 5-blade ceiling fan APBG5

SMHS000000000000

APBG5 5-Blade Industrial Ceiling Fan

- 5 Blades Extruded Aluminum Anodized Against Corrosion Constant Section
- Increased Air Distribution Cone
- Three-phase Brushless EC motor equipped with Integrated Electronic System and EMC filters
- 3 Sizes with Diameters 3.6m / 5.4m / 7.3m
- Air Flow Rates up to 438,818 m<sup>3</sup>/h (AMCA230-99)
- 110 RPM Max
- Pot. Max Ass. 0.75 kW



### Industrial 3-blade ceiling fan HVLS3

SLHS000000000000

HVLS 3-Blade Industrial Ceiling Fans.

- 3 Blades Extruded in Anodized Aluminum against Corrosion with Constant Cross Section
- Precabled 3-phase Brushless EC motor equipped with Integrated Electronic System and EMC3 filters



- Sizes with Diameters 2.4m / 3m / 3.6m
- Air Flow Rates up to 134,271 m<sup>3</sup>/h (AMCA230-99)200
- Max RPM
- Pot. Max Ass. 0.7 kW
- Suitable for continuous duty S1.

