

MFU filtered air exhaust connection on the outside

📌 Sectors

📌 Applications **Mobile**

📌 Issues **Fumes**

COD: KITSCARICESTMFU

Lateral connection diam. 200 mm for hose to discharge filtered air outside from MFU purifiers all.

Insight

With this hose connection, filtered air from MFU purifiers can be expelled into a flexible hose (to be purchased separately) so that it cannot be fed back into the room.


Kit contents:

- side panel for hose connection diam. 200

Optional/not included:

- flexible hose made of sturdy PVC reinforced with harmonic steel spiral diam. 200mm



**Kit contents:**

- side panel for connecting flexible hose, diameter 200

On request / not included:

- flexible hose in sturdy PVC reinforced with harmonic steel spiral, diameter 200 mm, 10 m lengths.



Dimensions

Code	Ø mm
KITSCARICESTMFU	200

Technical Data

Code	Pipe diameter mm	Attachment
KITSCARICESTMFU	200	200 mm diameter



Related Products



MFUHCO fume extractor

MFU21HCO0000000


MFUHCO high-performance mobile fume and exhaust extractor on wheels for professional use, with suction arm, HEPA H13 99.99% absolute filtration, and activated carbon filters.



MFU-HW welding fume extractor with superflex arm

MFU21HWXF000000

High-performance mobile welding fume extractor for professional use, with HEPA H13 99.99% absolute filtration



MFU-HW welding fume extractor with red arm

MFU21HWR0000000

MFU-HW mobile extractor for welding fumes and micro-dust with red arm, high performance for professional use, with HEPA H13 99.99% absolute filtration



MFU-HWF23 welding fume extractor double arm 3m

MFU21HW32F00000

MFU-HWF23 mobile welding fume extractor with double superflex arm, with H13 99.99% efficiency filtration.

