

Metal Filter Replacement - Stage 1 - MFU-HW

📌 Sectors

📌 Applications: **Mobile**

📌 Issues **Fumes**

COD: MFU21F001LS1M00



Metal Filter Replacement - Stage 1 - MFU-HW only

Detailed description

Solid construction and regenerable filter media, with anti-sparking function and protection of subsequent filters from coarse dust, frequent cleaning is recommended.

During assembly, special attention is paid to the insertion of the filter pack in order to make it integral to the frame and thus prevent the passage of dust.

Frame: galvanised steel

Protective netting: electro-welded galvanised steel wire on both sides

Filter media: metal mesh layers in aluminium cuspidated braid

Eurovent Class: EU 2 Average Arrestance Ashrae 52.1.1992

Maximum operating temperature: 200°C



Technical Data

| Code | Operating temperature °C | Frame | Protection nets | Filter baffle | Eurovent Class |
|-----------------|--------------------------|------------------|--|---|--------------------------------------|
| MFU21F00ILS1M00 | 200 | galvanised steel | on both sides electro-welded galvanised steel wire | Metal mesh layers in aluminium cuspidated braid | EU 2 Average arrest Ashrae 52.1.1992 |



Spare parts



Replacement acrylic filter - Stage 2 - MFU-HW

Replacement acrylic filter - Stage 2 - MFU-HW only



Replacement filter H13 HEPA - Stage 3 - MFU-HW

Replacement H13 HEPA filter - Stage 3 - MFU-HW only




Related products



MFU-HW welding fume extractor with superflex arm

MFU21HWXF000000

Mobile extractors for welding fumes and micro-dust, high performance for professional use, with HEPA H13 99.99% absolute filtration



MFU-HW welding fume extractor with red arm

MFU21HWR000000

Mobile extractors for welding fumes and micro-dust, high performance for professional use, with HEPA H13 99.99% absolute filtration

