

Desktop tin welding fume extractor with AFT filter

📌 Sectors [Welding](#),

📌 Applications [Fix](#)

📌 Issues [Fumes](#)

COD: AFT0000000000000



The **AFT tabletop fume extractor** captures fumes directly at the source through its special self-supporting flexible jointed hose before they can reach the operator's respiratory tract, as required by regulations. The AFT system is the ideal solution for small welding operations.

Insight

The AFT system is the ideal solution for small welding operations.

Pollutants are then filtered out by the BIA-class U.S.G.C.-certified polyester cartridge with 99% filtering efficiency and an activated carbon cartridge, both of which are integrated on the ejector port of the vacuum cleaner.

Its features result in:

- Space-saving
- Quiet
- Efficient
- Practical
- Can be oriented in all directions thanks to the rotating base
- Handy
- Extremely economical
- Lightweight

Construction and technical data

- Stable swivel pedestal to rest on work surface
- High-efficiency centrifugal aspirator
- Special 100-diameter flexible hose on suction, self-supporting and extendable at will
- Polyester cartridge filter eff.99% on air expulsion
- On/off switch with single-phase 220V cable and plug
- Nominal flow rate 200 mc/h
- Noise level 50 dB(A) at 1.5 mt
- Power 75W
- Weight kg 7



Technical Data

Code	Power kW	Nominal flow rate m ³ / h	Liv son Db (A)	Weight kg	Flex tube	Cartridge type	Aspirator
AFT000000000000	75	200	50	7	100 suction diameter, self-supporting and extendable at will	Polyester eff.99% on air expulsion	high efficiency centrifugal aspirator



Photogallery



Related spare parts



Activated carbon replacement cartridge for AFT

Original replacement activated charcoal filter cartridge for AFT vacuum cleaner



Polyester replacement cartridge for AFT

Original replacement polyester filter cartridge for AFT vacuum cleaner

